



K244E

HighSecLabs Secure 4-Port, Dual Display DVI-I KVM Switch



The **K244E** is a secure 4-port, DVI-I dual-display KVM switch. It provides the highest possible isolation between four connected computers each having two video output ports. The video ports support various video interfaces, from VGA to dual-link DVI and HDMI. Each computer may connect to up to two independent displays and operate in dual-display mode.

For enhanced security, a USB user authentication port (DPP) connects to a smart card or biometric reader. This requires the insertion of a physical authentication card or identification of a fingerprint to access the various computers/networks.

FEATURES

- **Dual-Display DVI-I Support** - Supports four computers each connected to two displays. Can drive VGA, HDMI and dual-link DVI video.
- **Biometric/Smart-Card Reader Support** - A special secured port (DPP) for a smart-card/biometric reader with patented freeze function, supports user authentication across multiple isolated networks.
- **Future-Proof** - Supports the widest range of video formats from VGA, single-link to 2560x1600 dual-link DVI and HDMI, supports latest keyboards, mice and all operating systems.
- **Highest Security by Design** - Common Criteria EAL 4+ approved, compatible with NIAP security requirements.
- **Hardware-Based Peripheral Isolation** - No dependency on firmware or software, all firmware on ROM, no keyboard buffering or memory.
- **Unidirectional Optical Data Diodes** - Assures USB peripheral isolation, data flows from devices to host only.
- **Display Plug & Play (DDC) Protection** - Leakage prevention through patented emulated technology, signaling attacks prevented by design, DDC/EDID fully functional.
- **Peripheral Security** - Full USB device filtering to assure support for keyboard and mouse only.
- **Active Anti Tampering System** - Always-on with 10 years battery, holographic tampering evident labels.

TECHNICAL SPECIFICATIONS

| | |
|--------------------------|--|
| HOST INPUT PORTS: | 4 DVI-I (F) connectors for primary video (VGA and HDMI supported), 4 DVI-I (F) connectors for secondary video (VGA and HDMI supported), 4 USB-B connector for keyboard and mouse, 4 3.5mm mini jack for unbalanced stereo audio, 4 USB-B dedicated peripheral ports (DPP). |
| CONSOLE PORTS: | 2 DVI-I (F) connector, 2 USB-A connectors for keyboard and mouse, 1 USB-A dedicated peripheral port (DPP), 2 DIN-5 connectors for PS/2 keyboard and mouse, 1 3.5mm mini jack for unbalanced stereo audio. |
| CHANNEL SWITCHING: | Front panel buttons, keyboard shortcuts. |
| SUPPORTED VIDEO MODES: | DVI dual-link resolutions up to 2560 x 1600, single-link DVI resolutions up to 1920x1200, VGA resolutions up to 2048x1536. HDMI supported through adapters or cables. |
| POWER CONSUMPTION: | 12V DC, 2.5A max. |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F). |
| STORAGE TEMPERATURE: | -40° to +60°C (-40° to 140°F). |
| HUMIDITY: | 10% to 90%, RHL non-condensing. |
| REGULATORY COMPLIANCE: | Safety: UL/cUL60950, EN60 950; EMI/EMC: FCC Class B, CE Mark, EN55022B, VCCI. |
| SECURITY ACCREDITATIONS: | Common Criteria EAL 4+ certified, complies with NIAP Peripheral Sharing Switch (PSS) For Human Interface Devices Ver 2.1. |
| INCLUDED ACCESSORIES: | Power supply. |
| PRODUCT DIMENSIONS: | 32.00cm x 13.00cm x 6.50cm (12.60" x 5.12" x 2.56") W, D, H |
| PRODUCT WEIGHT: | 1.8kg (4.0lbs) approx. |
| SHIPPING DIMENSIONS: | 45.00cm x 20.00cm x 12.00cm (17.72" x 7.87" x 4.72") W, D, H |
| SHIPPING WEIGHT: | 2.5kg (5.4lbs) approx. |