



## K308

### HighSecLabs Secure 8-Port KM Switch

---



The **K308** is a secure 8-port KM switch. It allows an easy yet secure sharing of keyboard and mouse between eight different security-level sources/computers. The **K308** provides the highest possible isolation between eight connected computers. HSL Virtual Display Technology (VDT) switches the **K308** seamlessly between computers once the mouse cursor crosses display borders. The **K308** works smoothly with all operating systems, from Microsoft to Linux and Apple with no need for software installation.

## FEATURES

---

- **Large KVM Switch** - For high-density environments, designed for rack mounting in data centers and server rooms.
- **Virtual Display Technology (VDT)** - Seamless keyboard, mouse and audio switching between computers once mouse cursor crosses display borders.
- **Display Configurations** - Arrives with a predefined preset of display configurations for ease of use. In addition, HSL VDT application allows administrators to configure any desired display configuration required.
- **Multiple-Head Support** - Can be easily configured to support dual/triple/multiple displays through HSL VDT application.
- **OS Independent** - Support for all Microsoft OS, Linux and Apple with no need for SW installation
- **Highest Security by Design** - Common Criteria EAL 4+ approved, compatible with NIAP security requirements.
- **Hardware-Based Peripheral Isolation** - No dependency on firmware or software, all firmware on ROM (Read Only Memory), no keyboard buffering or memory.
- **Unidirectional Optical Data Diodes** - Assures USB peripheral isolation, data flows from devices to host only.
- **Peripheral Security** - Full USB device filtering to assure support for keyboard and mouse only.
- **Active Anti-Tampering System** - Always-on with 10 years battery, holographic tampering evident labels.

TECHNICAL SPECIFICATIONS

---

HOST INPUT PORTS:	8 USB-B connector for keyboard and mouse, 8 3.5mm mini jack for unbalanced stereo audio.
CONSOLE PORTS:	2 USB-A connectors for keyboard and mouse, 1 3.5mm mini jack for unbalanced stereo audio.
CHANNEL SWITCHING:	Front panel buttons.
POWER:	90-240V AC.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +60°C (-40° to 140°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
SECURITY ACCREDITATIONS:	Common Criteria EAL 4+ ALC_FLR.3.
INCLUDED ACCESSORIES:	Power cord.
PRODUCT DIMENSIONS:	44.10cm x 17.40cm x 4.56cm (17.36" x 6.85" x 1.80" ) W, D, H
PRODUCT WEIGHT:	2.9kg (6.3lbs) approx.
SHIPPING DIMENSIONS:	55.00cm x 24.00cm x 17.00cm (21.65" x 9.45" x 6.69" ) W, D, H
SHIPPING WEIGHT:	4.2kg (9.3lbs) approx.