



TR-92

Dual Audio Transformer



The TR-92 is a 2x100W transformer for speaker signals. The unit takes two 4Ω/8Ω channels from a speaker output of a power amplifier, transforms them to 70/100V and distributes them to an array of loudspeakers.

FEATURES

- Bandwidth - 18kHz (-3dB).
- Max. Power - 100 watts.
- Passive Device - No power required.
- Desktop Size - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with an optional RK-1 adapter.



TR-92

TECHNICAL SPECIFICATIONS

INPUTS:	2 low-impedance ($4\Omega/8\Omega$) speaker inputs on terminal block connectors.
OUTPUTS:	2 high-impedance speakers on terminal block connectors.
MAX POWER:	100W.
VOLTAGE GAIN:	7.4dB/10.5dB (70V/100V).
BANDWIDTH (-3dB):	18kHz.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-10° to +60°C (14° to 140°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS	21.4cm x 16.2cm x 4.3cm (8.4" x 6.4" x 1.7") W, D, H.
WEIGHT:	2.85kg (10.7lbs).
OPTIONS:	RK-1 19" rack adapter.

