



## VP-427

### HDBaseT to HDMI ProScale™ Receiver/Scaler



The Kramer VP-427 is a receiver/scaler for HDBaseT twisted pair, HDMI, bidirectional RS-232 and IR signals. The unit receives an HDBaseT signal that it converts to HDMI, IR and RS-232 signals. It up- or down-scales the picture to match the resolution of the HDMI monitor.

## FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- Bidirectional RS-232 Port - For embedding/de-embedding control commands in the HDBaseT data stream.
- Infrared Input and Output Ports - For controlling devices over the HDBaseT data stream.
- System Range - Up to 70m (230ft).
- Embedded Audio - Support for LPCM 2CH.
- Constant Output Sync - Even when the input video signal is lost or interrupted.
- ProcAmp Control - Contrast, brightness, fine tune & R, G, B level/gain.
- On-Screen Display (OSD) - For easy setup and adjustment, accessible via the front-panel buttons.
- Non-Volatile Memory - Saves final settings.
- Freeze Button.
- USB Port - For upgrading firmware.



## VP-427

### TECHNICAL SPECIFICATIONS

INPUTS:	1 HDBaseT twisted pair on an RJ-45 connector, 1 IR on a 3.5mm mini jack.
OUTPUTS:	1 HDMI connector, 1 IR on a 3.5mm mini jack.
PORTS:	1 bidirectional RS-232 port on a 9-pin D-sub connector.
OUTPUT RESOLUTIONS:	NATIVE, VGA, SVGA, XGA, SXGA, UXGA, WXGA, WSXGA, WUXGA, 1600x900, 1400x1050, 1440x900, 1280x800, 1080i60, 1080p60, 1080p50, 1080i50, 720p60, 720p50, 576i, 576p, 480i, 480P.
OUTPUT REFRESH RATE:	60Hz for computer graphics resolutions, 50/60Hz for HDTV resolutions.
LATENCY:	30ms approx.
VIDEO COLOR DEPTH:	Input: 8/10/12-bit, output: 8-bit.
EMBEDDED AUDIO:	Supports LPCM 2CH.
RS-232 BAUDRATE:	115200bps max.
CONTROLS:	Front panel buttons, 1 USB for programming.
INDICATORS:	ON LED.
POWER CONSUMPTION:	5V DC, 1.5A.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
OPTIONS:	RK-T2B 19" rack adapter.
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	18.8cm x 11.4cm x 2.5cm (7.4" x 4.5" x 1.0") W, D, H.
WEIGHT:	0.45kg (1.0lb).
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-T2B 19" rack adapter.

