



VP-774AMP

9-Input HDMI & HDBaseT ProScale™ Presentation Switcher/Scalers with 2K Support and Audio Power Amplifier



The VP-774AMP is a high-performance presentation switcher and scaler. It accepts one of nine inputs: one DisplayPort (DP), one composite video, two computer graphics, one 3G HD-SDI and four HDMI signals. It scales the video, embeds the audio, and simultaneously outputs the signal to two identical HDMI, one HDBaseT and one 3G HD-SDI output, together with S/PDIF and balanced stereo audio outputs. The unit also includes an audio amplifier and speaker outputs.

FEATURES

- **K-IIT XL™ Picture-in-Picture Image Insertion Technology** - Ultra-stable picture-in-picture, picture-and-picture, and split screen capability. Any video source can be inserted into or positioned next to any other video source with full window positioning and sizing controls.
- **Kramer's PixPerfect™ Scaling Technology** - Kramer's precision pixel mapping and high quality scaling technology. High-quality 3:2 and 2:2 pull down de-interlacing and full up- and down-scaling of all video input signals.
- **State-of-the-Art Video Processing Technology** - For highest quality de-interlacing, noise reduction, and scaling performance for both standard-definition and high-definition signals.
- **Ultra-Fast Fade-Thru-Black (FTB™) Switching** - Video switching transitions are clean and ultra fast. The video fades to black and the new input fades from black for smooth, glitch-free switching. The output signal provides constant sync so the display never glitches.
- **HDCP Compliant** - The HDCP (High Definition Content Protection) license agreement allows copy-protected data on the HDMI input to pass only to the HDMI output.
- **Advanced EDID Management** - Per input; analyzes the EDID of a selectable Master connection to one of the outputs.
- **Mass Notification Emergency Communication System (MNEC)** - Activates a national or campus-wide notification, immediately displayed when an emergency situation develops. It uses automatic text overlaying, either via a crawler or a full screen cover up, as well as an optional audio alert.
- **Max. Data Rate** - 6.75Gbps (2.25Gbps per graphic channel).
- **Multi-Standard SDI Support** - SDI (SMPTE 259M), HD-SDI (SMPTE 292M) and 3G HD-SDI (SMPTE 424M).
- **Scaled Outputs** - 2 HDMI, 1 HDBaseT, 1 3G HD-SDI (all outputs work simultaneously).
- **Output Resolutions** - HDTV and computer graphics up to 2K and 1080p/UXGA with selectable refresh rates.
- **HDMI Deep Color Support** - For all inputs and outputs.
- **Luma Keying** - Via PIP window.
- **Vertical Keystone Operation.**
- **Built-in Proc-Amp** - With enhanced functions such as color correction, gamma and dither.

- **Multi-Standard Video Support** - NTSC (3.58/4.43), PAL (M/N/60) and SECAM with advanced de-interlacing options.
- **Built-in Time Base Corrector** - Stabilizes unstable video sources.
- **Picture Zooming** - Both on main and PIP window from 100% to 1600%, including separate V and H sharpness control.
- **Input and Output Colorspace Control.**
- **Audio Support** - Unbalanced stereo audio inputs, with two microphone inputs; digital stereo and balanced stereo outputs; input and output audio level adjustment.
- **Selectable Microphone Talkover or Mix Modes.**
- **Microphone Inputs** - 2 dynamic or condenser (with 48V phantom voltage).
- **Audio Amplifier & Speaker Output** - 2x10W.
- **Automatic Detection and Selection of Embedded Audio** - Automatically outputs the signal from the HDMI and DP embedded audio inputs or performs an analog takeover to output the respective analog audio input.
- **Range** - Up to 130m (430ft) normal mode; up to 180m (590ft) ultra mode (1080p @60Hz @24bpp) when using BC-HDKat6a cables.
- **On-Screen Display (OSD)** - For easy setup and adjustment, accessible via the IR remote control and via the front-panel buttons.
- **Built-in Web Page Server.**
- **Non-Volatile Memory** - Saves final settings.
- **Firmware Upgrades** - Via Ethernet and RS-232.
- **Flexible Control Options** - Front panel buttons, OSD (on-screen display) via front panel buttons or IR remote (remote control included), embedded Web server.
- **Port Tunneling** - A bidirectional RS-232 interface where simple control commands and data can flow in both directions from a controller to the VP-773 via the Ethernet, allowing status requests and control of the destination unit
- **Selectable Power Save Modes** - For efficient energy use.
- **Worldwide Power Supply** - 100-240V AC.
- **Standard 19" Rack Mount Size** - 1U. Rack "ears" included.

CONTROLS: Front panel buttons, OSD, IR remote control, RS-232 on a 9-pin D-sub connector, Ethernet.

OPERATING TEMPERATURE: 0° to +40°C (32° to 104°F).

STORAGE TEMPERATURE: -40° to +70°C (-49° to 158°F).

HUMIDITY: 10% to 90%, RHL non-condensing.

POWER SOURCE: 100-240V AC, 40VA max.

DIMENSIONS: 19" x 9.3" x 1U (W, D, H) rack mountable.

WEIGHT: 3kg (6.6lbs) approx.

INCLUDED ACCESSORIES: Power cord, rack "ears", IR remote control.

