



VS-44AV

4x4 Composite Video & Stereo Audio Mechanical Switcher



The **VS-44AV** is a high-performance switcher (four crosspoints) for composite video and unbalanced stereo audio signals. It routes up to four inputs to four different individual outputs (not to multiple outputs).

FEATURES

- Bandwidth - 220MHz (-3dB).
- Mechanical (Passive) Switching - No power required.
- Standard 19" Rack Mount Size - 1U.



VS-44AV

TECHNICAL SPECIFICATIONS

INPUTS:	4 video, 1Vpp/75Ω on BNC connectors; 4 unbalanced stereo audio, up to +4dBu (typ.) on RCA connectors.
OUTPUTS:	4 composite video, 1Vpp/75Ω on BNC connectors. 4 unbalanced stereo audio, up to +4dBu (typ.) on RCA connectors.
SWITCHING SYSTEM:	Mechanical, break-before-make.
BANDWIDTH (-3dB):	Video: 220MHz; Audio: 100kHz.
CROSSPOINTS:	16 for video, 16x2 for audio, 4 active at any given time.
VIDEO CROSSTALK:	-46dB @5MHz.
SIGNAL LEVELS:	Up to 3Vpp video, +30dBu audio.
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	1.6kg (3.5lbs) approx.

