



VS-4YC

4x4 s-Video & Stereo Audio Switcher



The **VS-4YC** is a high-performance single crosspoint switcher for s-Video (Y/C) and unbalanced audio signals. It independently switches any one of four audio or s-Video (Y/C) signals to a single audio or video output.

FEATURES

- Bandwidth (Y) - 280MHz (-3dB)
- Mechanical (Passive) Switching - No power required
- Separate Audio & s-Video Switching - 1 crosspoint (each)
- Desktop Size - Compact size. Two units can be rack mounted side-by-side in a 2RU rack space with the optional RK-4E/S adapter



VS-4YC

TECHNICAL SPECIFICATIONS

INPUT:	4 s-Video, 1Vpp/75Ω (Y), 0.3Vpp/75Ω (C) on 4-pin connectors. 4 unbalanced stereo audio, up to 36Vpp on RCA connectors.
OUTPUTS:	4 s-Video, 1Vpp/75Ω (Y), 0.3Vpp/75Ω (C) on 4-pin connectors; 4 unbalanced stereo audio, up to 36Vpp on RCA connectors.
BANDWIDTH (-3dB):	Video: 280MHz(Y), audio: 100kHz.
SWITCHING SYSTEM:	Mechanical, break-before-make.
CROSSTALK:	-42dB chrominance, -60dB sync.
DIMENSIONS:	18.8cm x 7cm x 7cm (7.4" x 2.7" x 2.7") W, D, H.
WEIGHT:	0.6kg (1.3lbs) approx.
OPTIONS:	19" rack adapter RK-4E/S.

