



VS-611

6x1 Composite Video & Balanced Stereo Audio Switcher



The **VS-611** is a high-performance switcher for composite video and balanced audio signals. Switching during the vertical interval ensures glitch-free switching with genlocked sources.

FEATURES

- Bandwidth - 250MHz (-3dB).
- Vertical Interval Switching.
- Switching Synchronization - Synchronizes either to external reference or the incoming video.
- Control - Front panel RS-232 (K-Router™ Windows®-based software is included), RS-485, & contact closure.
- Standard 19" Rack Mount Size - 1U.



VS-611

TECHNICAL SPECIFICATIONS

INPUTS:	6 composite/single component video, 1Vpp/75Ω, on BNC connectors. 6 audio balanced stereo, +4dBu, 10kΩ, on 2-part, snap fit terminal blocks; 1 external sync input (or composite video) 1Vpp/75Ω, on a BNC connector.
OUTPUT:	1 composite/single component video, 1Vpp/75Ω on a BNC connector; 1 audio balanced stereo up to +28Vpp/50Ω, (24dBu) on terminal blocks.
BANDWIDTH (-3dB):	Video: 250MHz (typical); Audio: 55kHz.
DIFF. GAIN:	0.04%.
DIFF. PHASE:	0.03Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	Video: 77.6dB; Audio: 95dB, unweighted.
NON-LINEARITY:	0.1%.
AUDIO CROSSTALK:	-79dB.
AUDIO THD+NOISE:	0.02%.
2nd HARMONIC:	0.003% (1kHz).
CONTROL:	12 illuminated front-panel touch switches, RS-232, RS-485 and contact closure.
POWER SOURCE:	230V AC, 50/60Hz, (115V AC USA).
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	3.1kg (6.88lbs) approx.
ACCESSORIES:	Power cord, Windows®-based control software, null-modem adapter.

