




WP-110xl

Active Wall Plate – Computer Graphics Video over Twisted Pair Transmitter with EDID



The WP-110xl is an extended range wall plate transmitter for computer graphics video signals with resolutions up to and exceeding UXGA. It converts a computer graphics video signal into a twisted pair signal that it transmits to a compatible Kramer receiver.

FEATURES

- HDTV Compatible.
- Max. Resolution - WUXGA & 1080p.
- Extended Transmission Range - Up to 250m (820ft).
- EDID Capture - Copies and stores the EDID from a display device.
- Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other.
- Increased Interference Protection - Against noise, spikes and interference in adverse environments.
- Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5.
- Dimensions - 11.4cm x 3.5 cm x 11.4cm (4.49" x 1.4" x 4.49") US; 15.2cm x 3.5cm x 8.0/8.6cm (5.98" x 1.4" x 3.15/3.39") EU W, D, H.



WP-110xl

TECHNICAL SPECIFICATIONS

| | |
|------------------------|---|
| INPUT: | 1 VGA/UXGA on a 15-pin HD connector. |
| OUTPUT: | 1 twisted pair on an RJ-45 connector. |
| VIDEO RESOLUTION: | Up to WUXGA, 1080p. |
| RANGE: | Up to 250m (820ft). |
| COUPLING: | AC. |
| POWER CONSUMPTION: | 12V DC, 70mA. |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F). |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F). |
| HUMIDITY: | 10% to 90%, RHL non-condensing. |
| WALL PLATE SIZE: | 2 gang EU/US. |
| DIMENSIONS: | 2 gang USA: 11.4cm x 3.5 cm x 11.4cm (4.49" x 1.4" x 4.49") W, D, H 2 gang EU: 15.2cm x 3.5cm x 8.0/8.6cm (5.98" x 1.4" x 3.15/3.39") W, D, H. |
| WEIGHT: | 0.14kg (0.31lbs) approx. |
| INCLUDED ACCESSORIES: | Power supply. |
| OPTIONS: | 19" rack adapters for EU and US wall plates; Kramer on-wall boxes. |

