




WP-110xl

Active Wall Plate - Computer Graphics Video over Twisted Pair Transmitter with EDID



The **WP-110xl** is an extended range wall plate transmitter for computer graphics video signals with resolutions up to and exceeding UXGA. It converts a computer graphics video signal into a twisted pair signal that it transmits to a compatible Kramer receiver.

FEATURES

- **HDTV Compatible.**
- **Max. Resolution - WUXGA & 1080p.**
- **Extended Transmission Range - Up to 250m (820ft).**
- **EDID Capture - Copies and stores the EDID from a display device.**
- **Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other.**
- **Increased Interference Protection - Against noise, spikes and interference in adverse environments.**
- **Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5.**
- **Dimensions - 11.4cm x 3.5 cm x 11.4cm (4.49" x 1.4" x 4.49") US; 15.2cm x 3.5cm x 8.0/8.6cm (5.98" x 1.4" x 3.15/3.39") EU W, D, H.**



WP-110xl

TECHNICAL SPECIFICATIONS

INPUT:	1 VGA/UXGA on a 15-pin HD connector.
OUTPUT:	1 twisted pair on an RJ-45 connector.
VIDEO RESOLUTION:	Up to WUXGA, 1080p.
RANGE:	Up to 250m (820ft).
COUPLING:	AC.
POWER CONSUMPTION:	12V DC, 70mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
WALL PLATE SIZE:	2 gang EU/US.
DIMENSIONS:	2 gang USA: 11.4cm x 3.5 cm x 11.4cm (4.49" x 1.4" x 4.49") W, D, H 2 gang EU: 15.2cm x 3.5cm x 8.0/8.6cm (5.98" x 1.4" x 3.15/3.39") W, D, H.
WEIGHT:	0.14kg (0.31lbs) approx.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	19" rack adapters for EU and US wall plates; Kramer on-wall boxes.

