



TBUS-2

Table Mount Pass-Thru System With Hydraulic Tilt



The **TBUS-2** is a rectangular table-mount cable management system for boardrooms and conference rooms. It opens/closes by pressing down gently on the lid which hydraulically raises the **TBUS-2** connectors for easy access and connection.



TBUS-2

FEATURES

- **Hydraulic Lift** - Easy opening & closing by pressing down gently on the cover. When not in use, it lowers flush with the table.
- **Power Input** - International, USA and European power sockets available.
- **Elegant and Rugged Rectangular Design** - The sturdy and attractive anodized aluminum enclosure is designed to provide maximum connectivity in the smallest possible footprint, at the same time cost effective and easy to install.
- **Modular Design** - 5 wall plate insert slots (6 in USA).
- **Easy Installation** - Requires tools and expertise to cut a 240.54 x 156.13mm (9.47" x 6.03") rectangular hole in the surface of the furniture. Maximum table thickness is 76mm (3in).

TECHNICAL SPECIFICATIONS

POWER SOURCE (AC power limits): Dual US 110V AC, 60Hz, 2.5A per connector. Australia 220-240V AC, 50/60Hz, 5A per connector. Germany and the EU 220-240V AC, 50/60Hz, 5A per connector. Belgium and France 220-240V AC, 50/60Hz, 5A per connector. The UK 220-240V AC, 50/60Hz, 5A per connector. South Africa 220-240V AC, 50/60Hz, 5A per connector. Italy 220-240V AC, 50/60Hz, 5A per connector.

DIMENSIONS: Including the outer rim: 25.3cm x 16.6cm x 18.4cm (9.97" x 6.53" x 7.25") W, D, H. Without the outer rim: 24.054cm x 15.613cm x 18.4cm (9.47" x 6.03" x 7.25") W, D, H.

WEIGHT: 1.15kg (2.53lbs) approx.

ACCESSORIES: Power cord.

OPTIONS: Kramer inserts and interfaces.